


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : B65D 55/02	A1	(11) International Publication Number: WO 00/66451 (43) International Publication Date: 9 November 2000 (09.11.00)
(21) International Application Number: PCT/GB00/01609 (22) International Filing Date: 26 April 2000 (26.04.00) (30) Priority Data: 9910143.8 30 April 1999 (30.04.99) GB (71) Applicant (for all designated States except US): AUDUS NOBLE LTD. [GB/GB]; Blyth Industrial Estate, Cowpen Road, Blyth, Northumberland NE24 5TD (GB). (72) Inventors; and (75) Inventors/Applicants (for US only): THOMPSON, David, Noble [GB/GB]; 32 Beverley Gardens, Cullercoats, North Shields, Tyne & Wear NE30 4NS (GB). BUSHBY, Stephen, William [GB/GB]; 2 Delaval Court, Bedlington, Northumberland NE22 5YL (GB). STEPHENSON, Keith [GB/GB]; 46 Eastern Way, Darras Hall, Ponteland, Newcastle Upon Tyne (GB). (74) Agents: SANDERSON, Michael, J. et al.; Mewburn Ellis, York House, 23 Kingsway, London WC2B 6HP (GB).		(81) Designated States: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>

(54) Title: TAMPER-EVIDENT CONTAINER**(57) Abstract**

A tamper-evident container comprises a body portion (2), a lid portion (4) adapted to engage and close said body portion (2), and at least one tamper-evident element (14) releasably attached to one of said portions (4) by a weakened connection (16), and having an operative position co-operating with means on the other of said portions (2) to prevent removal of the lid portion (4) from the body portion (2), the lid portion (4) only being removable from the body portion (2) subsequent to breakage of the weakened connection (16) between the or each tamper-evident element (14) and the one portion (4) of the container, the or each tamper evident element (14), on breakage, having a displaced position on the other portion (2) of the container providing a visual indication that tampering may have occurred, and the container incorporating means to retain the or each tamper-evident element (14) in its displaced position on the other portion (2) of the container such that removal of the or each tamper-evident element (14) from its displaced position cannot be effected without damage to the element (14).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon	KR	Republic of Korea	PL	Poland		
CN	China	KZ	Kazakhstan	PT	Portugal		
CU	Cuba	LC	Saint Lucia	RO	Romania		
CZ	Czech Republic	LI	Liechtenstein	RU	Russian Federation		
DE	Germany	LK	Sri Lanka	SD	Sudan		
DK	Denmark	LR	Liberia	SE	Sweden		
EE	Estonia			SG	Singapore		

TAMPER-EVIDENT CONTAINERTECHNICAL FILED

5 This invention relates to tamper-evident containers
and more particularly to containers provided with
elements thereon for indicating whether or not the
container has been tampered with prior to initial use.

BACKGROUND TO THE INVENION

10 In order to attempt to counter modern trends
towards sabotaging the contents of certain containers,
particularly those containing materials to be consumed
or to be used on babies or infants, it is becoming
increasingly necessary to provide visual evidence in or
15 on the containers that they have not been opened or
tampered with prior to use of the contents.

Although tamper evident means are well-established
on containers such as bottles with round lids, the
provision of such means on rectangular, box-like
20 containers comprising separate or hinged box portions
and lid portions poses more of a problem.

It is known to provide sealed foil covers on the
box portion below the lid portion to protect the
contents of the container, but such foil seals are not
25 visible until the lid portion is removed from the box
portion.

GB 2239 866 discloses a box-like container provided
with tamper evident members frangibly secured to the lid

portion and co-operating with the box portion normally to prevent removal of the lid portion from the box portion. When the tamper evident members are pressed down, the frangible connection with the lid portion is broken and the lid portion can be removed from the box portion.

However, the tamper evident elements, once the frangible connections are broken, become separate from the container and must be disposed of. Clearly such disposal, particularly where there are a plurality of elements each of which must be broken away to achieve opening of the container, is inconvenient.

SUMMARY OF THE INVENTION

It would be desirable to be able to provide a container the tamper evident elements of which do not require disposal as heretofore.

According to the present invention there is provided a tamper-evident container comprising a body portion, a lid portion adapted to engage and close said body portion, and at least one tamper-evident element releasably attached to one of said portions by a weakened connection, the or each tamper-evident element having an operative position on the container co-operating with means on the other of said portions such as to prevent removal of the lid portion from the body portion, the arrangement being such that the lid portion can only be removed from the body portion subsequent to

breakage of the weakened connection between the or each tamper-evident element and the one portion of the container, characterised in that the or each tamper evident element, on breakage, has a displaced position
5 on the other portion of the container providing a visual indication that tampering may have occurred, the container incorporating means to retain the or each tamper-evident element in its displaced position on the other portion of the container such that removal of the
10 or each tamper-evident element from its displaced position cannot be effected without damage to the element, thereby making it difficult or impossible to hide the fact that the tamper-evident elements have been disturbed.

15 In one embodiment of the invention the respective portions of the container have co-operating rims on part or the whole of their co-operating peripheries. The tamper-evident elements may be incorporated in these rims, preferably in the lid portion.

20 Conveniently the rim of the body portion is of substantially inverted U-shape in transverse section and includes, for the or each tamper-evident element, an aperture in the upper wall thereof, said element, in its operative position, projecting from said aperture above
25 the upper wall of the rim of the body portion, breakage of the or each weakened connection being achieved by forcible depression of the or each tamper-evident element into a displaced position, in which displaced

position the or each element is housed within the rim of the body portion with the upper wall of the tamper-evident element being substantially co-planar with the upper wall of the rim of the body portion to be visible through the associated aperture in said rim of the body portion.

In an alternative embodiment of the invention, the container comprises a body portion having a reduced diameter neck, and a lid portion which is a push snap-fit onto the neck of the body portion, the or each tamper-evident element being connected by a weakened connection to the lower edge of the lid portion to depend therefrom, the neck of the body portion having formed thereon, one for each tamper-evident element, a hollow box-like receiving member into which the associated tamper-evident element extends to be contained thereby in the operative position of said element, the or each tamper-evident element and the or each receiving member having co-operating surfaces thereon preventing relative axial movement between the lid portion and the body portion, the arrangement being such that, on forcible removal of the lid portion from the body portion, the or each weakened connection is broken and the or each tamper-evident element falls to a displaced position projecting from the associated receiving member to provide a visual indication of said removal.

Conveniently the displaced position of a tamper-

evident element within the receiving member is determined by abutment of the lower end of the element with a shoulder on the body portion below the neck thereof.

5 Preferably the or reach tamper-evident element is integrally moulded with its associated container portion and is connected thereto by means of at least one strip member extending between said element and said portion, the connection between the strip member and the
10 container portion being weaker than the connection between the strip member and the element.

BRIEF DESCRIPTION OF THE DRAWINGS

15 Figs. 1 and 2 are scrap vertical sections through part of the lid portion, body portion and tamper-evident element of a first container according to the invention in the operative position and displaced position respectively of the tamper-evident element;

20 Figs. 3 and 4 are isometric views of the parts of the container shown in Figs. 1 and 2 respectively;

 Fig. 5 is a plan view from above of a tamper-evident element of the container of Figs 1 and 2 showing the means of connection to the rim of the lid portion;

25 Fig. 6 is an isometric view of a closed second container according to the invention;

 Fig. 7 is an isometric view, partly cut away, of the tamper evident element of the container of Fig. 6 with the lid portion removed;

Fig. 8 is a vertical section through a third container according to the invention, and

Fig. 9 is a detail of Fig. 8.

5 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to Figs 1 to 5 of the drawings, the illustrated first container comprises a box portion 2 to which is hingedly mounted a lid portion 4. The box portion 2 is provided with a peripheral rim 6 of
10 substantially inverted U-shape in transverse section, said rim 6 including a substantially horizontal top wall 8 and a depending outer sidewall 10.

The lid portion 4 includes a substantially horizontal peripheral rim 12, the rims 6 and 12 being
15 integrally moulded with the associated portion 2,4 of the container.

Integrally moulded with the rim 12, one to each side of the container, are a pair of tamper-evident elements indicated generally at 14, each element 14
20 being substantially U-shape in transverse section. The elements 14 are each connected to the rim 12 by a number of tapering strips 16 integrally moulded with the rim 12 and the element 14 and extending between the element 14 and the rim 12, the area of connection between each
25 strip 16 and the rim 12 being substantially less than that between the strip 16 and the element 14.

The elements 14 each comprise opposed sidewalls 18,20 and a top wall 22 and, in the operative position

of an element 14 shown in Figs. 1,3 and 6, the bulk of the element is upstanding from the rim 12 of the lid portion 4, only the free ends of the sidewalls 18,20 depending below the plane of the rim 12. The free end
5 of the sidewall 20 is provided with an outwardly-projecting flange 24 thereon for reasons which will become apparent.

The rim 6 of the box portion 2 is provided with a pair of apertures in the top wall 8 thereof, one located
10 below each of the elements 14 on the lid portion 4, and said apertures being shaped to receive therein the lower regions of the elements 14 in their operative positions.

More particularly, on closure of the container and with the elements 14 in their operative positions,
15 sidewalls 18,20 of the elements 14 pass through the associated apertures in the rim 6, the flange 24 on the sidewall 20 snapping under the defining edge of the aperture in the top wall 8 of the rim 6, as seen in Fig. 1, to lock the lid portion 4 to the box portion 2 and to
20 prevent opening of the container.

Thus the upstanding positions of the elements 14 indicate the factory-produced, normally closed position of the container prior to initial opening thereof.

In order to open the container, the elements 14 are
25 each pressed downwardly relative to the rim 12 of the lid portion 4 whereby the weakened connection between the strips 16 and the rim 12 are broken and the elements 14, together with the strips 16 integral therewith, are

each displaced bodily downwardly into the position shown in Figs. 2 and 4 housed within the rim 6 of the box portion 2.

The internal configuration of the rim 6 is such as to provide an abutment 26 for the free end of the sidewall 18 of the element 14 and a co-operating undercut shoulder 28 for engagement by the flange 24 on the sidewall 20 of the element 14, whereby the element 14 is positively retained in its displaced position within the rim 6 with the upper surface of the top wall 22 of the element 14 lying substantially co-planar with the upper surface of the rim 12 of the lid portion - the co-operation between the flange 24 and the shoulder 28 prevents return of the element 14 from its displaced position towards its operative position.

Thus it will be appreciated that the positions of the elements 14 give a visual indication of the condition of the container, a supposedly unopened container in which the elements 14 are in their displaced positions indicating it has possibly been tampered with. Furthermore, the retention of the elements 14 in their displaced positions eliminates the necessity to dispose of the elements once the container is legally opened for normal use.

Clearly the precise number, location and configuration of the tamper-evident elements 14 can be varied to suit particular requirements providing there is a weakened connection between each element 14 and the

rim 12 of the lid portion to enable displacement of the element from its operative position locking the container to a retained position permitting opening of the container and providing visual evidence of the condition of the container.

The container may comprise a detachable lid that is removable to open the container, or may have a captive lid, retained for example by separate or integral hinge means.

Fig. 6 shown a box-like container according to the invention in its closed condition and in which the lid portion 4 is retained on the box portion 2 thereof by an opposed pair of tamper evident elements 14 carried by the lid portion 4, one to each end of the container, and depending through associated apertures in the rim of the box portion 2 substantially as detailed above with reference to Figs. 1 to 5.

However, the means for retaining an element 14 in its displaced position differ from those of the container of Figs 1 to 5 as can be seen from Fig. 7.

Referring to Fig. 7, the box portion 2 includes a rim in the form of a box - like receiving sleeve 30 integrally moulded with each opposed side wall of the portion 2 and adapted to receive the tamper evident element 14 in its displaced position. A vertical rib 32 extends between the wall of the sleeve 30 and the wall of the box portion 2, the tamper evident element 14 having an upwardly tapering vertical groove 34 formed

centrally therein.

The displaced position of the tamper evident element 14 is determined by co-operation between the rib 32 and the groove 34 as can be seen in Fig. 7, this co-operation retaining the tamper evident element 14 in its displaced position in which the top thereof is visible above the sleeve 30.

Referring to Figs 8 and 9 of the drawings there is shown an alternative container according to the invention comprising a rectangular section body portion 102 having a reduced dimensional neck 104 above a defining shoulder 106 on the body portion. The container is completed by a lid portion 108 which is a push snap fit on the neck 104.

A pair of diametrically-opposed tamper-evident elements in the form of clips 110 depend from the rim of the lid portion 108, each clip 110 being connected to the lid portion by a series of thin tabs 112. Each clip 110 is formed at its free end with an outwardly facing hook portion 114 having a horizontal surface thereto.

A corresponding pair of hollow, box-like housings 116 are integrally moulded on the external surface of the neck 104, each adapted to receive therein an associated one of the clips 110.

The internal face of the outer wall of each housing 116 is formed with an undercut having a horizontal surface thereto, the arrangement being such that, with the lid portion 108 of the container positioned on the

neck 104 of the body portion 102, the clips 110 are received within associated housings 116 and the horizontal surfaces of the clips 110 and the housings 116 co-operate with one another to prevent removal of the lid portion 108 from the body portion 102.

Opening of the container is achieved by forcible upward movement of the lid portion 108 whereby the tabs 112 are broken to release the lid portion 108 from the neck 104, the clips 110 remaining within their associated housings 116 because of the co-operation between the horizontal surfaces thereon.

Subsequent to breakage of the tabs 112, the clips 110 each fall under gravity to a position determined by abutment of the lower end of the hook portion 114 with the shoulder 106, in which position the stem of a clip 110 remains within the associated housing 116 but the hook portion 114 projects therefrom to provide a visible indication that the lid portion 108 has been removed from the body portion 102.

Clearly the precise construction of the container of Figs. 8 and 9 can be varied from that described and illustrated. In particular the number and locations of the clips 110 and housings 116 can be varied to suit particular requirements, as can the particular construction of the clips 110 and housings 116 and the locking means preventing removal of the clips 110 from the housings 116.

CLAIMS

1. A tamper-evident container comprising a body portion (2), a lid portion (4) adapted to engage and close said body portion (2), and at least one tamper-evident element (14) releasably attached to one of said portions (4) by a weakened connection (16), the or each tamper-evident element (14) having an operative position on the container co-operating with means on the other of said portions (2) such as to prevent removal of the lid portion (4) from the body portion (2), the arrangement being such that the lid portion (4) can only be removed from the body portion (2) subsequent to breakage of the weakened connection (16) between the or each tamper-evident element (14) and the one portion (4) of the container, characterised in that the or each tamper evident element (14), on breakage, has a displaced position on the other portion (2) of the container providing a visual indication that tampering may have occurred, the container incorporating means (26) to retain the or each tamper-evident element (14) in its displaced position on the other portion (2) of the container such that removal of the or each tamper-evident element (14) from its displaced position cannot be effected without damage to the element (14).

2. A tamper-evident container as claimed in claim 1 in which the respective portions of the container have

co-operating rims (6,12) on part or the whole of their co-operating peripheries.

3. A tamper evident container as claimed in claim
5 2 in which the tamper-evident elements (14) are incorporated in the rims (6,12), preferably in the lid portion (4).

4. A tamper evident container as claimed in claim
10 2 or claim 3 in which the rim (6) of the body portion (2) is of substantially inverted U-shape in transverse section and includes, for the or each tamper-evident element (14), an aperture in the upper wall thereof, said element (14), in its operative position, projecting
15 from said aperture above the upper wall (8) of the rim (6) of the body portion (2), breakage of the or each weakened connection (16) being achieved by forcible depression of the or each tamper-evident element (14) into a displaced position, in which displaced position
20 the or each element (14) is housed within the rim (6) of the body portion (2) with the upper wall (22) of the tamper-evident element (14) being substantially coplanar with the upper wall (8) of the rim (6) of the body portion (2) to be visible through the associated
25 aperture in said rim (6) of the body portion (2).

5. A tamper-evident container as claimed in claim
4 in which the retaining means comprises an abutment

(26) projecting outwardly from the body portion (2) within the rim (6) thereof.

5 6. A tamper-evident container as claimed in claim 4 or claim 5 in which the rim (6) of the body portion (2) is provided with locking means (28) to prevent upward movement of the or each element (14) from its displaced position.

10 7. A tamper-evident container as claimed in claim 4 in which the retaining means comprises at least one rib (32) within the rim (30) adapted to receive thereon, and locate, the temper-evident element (14) in its displaced position.

15



 8. A tamper-evident container as claimed in claim 1 and comprising a body portion (102) having a reduced diameter neck (104), and a lid portion (108) which is a push snap-fit onto the neck (104) of the body portion (102), the or each tamper-evident element (110) being connected by a weakened connection (112) to the lower edge of the lid portion (108) to depend therefrom, the neck (104) of the body portion (102) having formed thereon, one for each tamper-evident element (110), a
20 hollow box-like receiving member (116) into which the associated tamper-evident element (110) extends to be contained thereby in the operative position of said
25 element (110), the or each tamper-evident element (110)

and the or each receiving member (116) having co-operating surfaces thereon preventing relative axial movement between the lid portion (108) and the body portion (102), the arrangement being such that, on
5 forcible removal of the lid portion (108) from the body portion (102), the or each weakened connection (112) is broken and the or each tamper-evident element (110) falls to a displaced position projecting from the associated receiving member (116) to provide a visual
10 indication of said removal.

9. A tamper-evident container as claimed in claim 8 in which the displaced position of a tamper-evident element (110) within the receiving member (116) is
15 determined by abutment of the lower end (114) of the element (110) with a shoulder (106) on the body portion (102) below the neck (104) thereof.

10. A tamper-evident container as claimed in any
20 one of claims 1 to 9 in which the or each tamper-evident element (14) is integrally moulded with its associated container portion (4) and is connected thereto by means of at least one strip member (16) extending between said element (14) and said portion (4), the connection
25 between the strip member (16) and the container portion (4) being weaker than the connection between the strip member (16) and the element (14).

1/5



2/5




Fig.3




Fig.4




Fig.5

3/5




Fig. 6

4/5




Fig. 7




Fig. 9

5/5




Fig. 8

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 00/01609

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 B65D55/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB 2 239 866 A (LAWSON MARDEN) 17 July 1991 (1991-07-17) the whole document	1-4, 6, 8, 10
A	EP 0 658 486 A (MOULAGES DU VELAY) 21 June 1995 (1995-06-21) column 3, line 56 -column 4, line 31; figures 4-6	1-10
A	EP 0 875 210 A (DDS SANIFICAZIONE) 4 November 1998 (1998-11-04) abstract; figures	1-4, 10



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

14 July 2000

Date of mailing of the international search report

24/07/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Gino, C

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 00/01609

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
GB 2239866	A	17-07-1991	NONE	
EP 658486	A	21-06-1995	FR 2713602 A	16-06-1995
EP 875210	A	04-11-1998	IT MI971023 A	30-10-1998